(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 14 June 2001 (14.06.2001)

PCT

(10) International Publication Number WO 01/42546 A1

(51) International Patent Classification7:

Stefaan [BE/BE]; Avelgemstraat 152, B-8550 Zwevegem (BE).

(21) International Application Number:

PCT/EP00/11775

D03C 3/20

(22) International Filing Date: 7 December 2000 (07.12.2000)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

mber 1999 (08.12 BE

9900803

(71) Applicant (for all designated MICHEL VAN DE WIELE BE/BE]; Michel Vandewielestraat 7/17, B-8510 Kortrijk/Marke (BE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): VANHEESBEKE,

(74) Agent: KOB NV; Leherte, Georges, Kennedypark 31C, B-8500 Kortrijk (BE).

(81) Designated States (national): JP, KR, US.


(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

Published:

With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND DEVICE FOR CONTROLLING A SELECTION DEVICE WITH SOLENOIDS FOR A WEAVING MACHINE



(57) Abstract: Device for energising a number of coils (1) of a hook selection device for a weaving machine, comprising an electrical power supply source (V1) connected to the coils (1) and a regulating device for regulating the current intensity in the coils, comprising for each coil: a comparator (3) for comparing the current intensity in the coil (1) to a reference current intensity, and a controllable current regulator (e.g. a chopper transistor (M1)) provided for regulating the current intensity in the coil (1) in order to reach or approach this reference current intensity, whereas said regulating device comprises an electronic control circuit (2a, 2b) that is provided to control the current regulator (M1) of each coil (1) of a number of coils, in order to reduce a variance between the actual current intensity in that coil (1) and the reference current intensity measured by the comparator (3) of that coil (1).